

B3/T

3" MULTIPOINT SPEAKER



B3/T system is a multipoint speaker designed to be discreet and elegant.

Thanks to its performance, sound quality and exceptional reliability, **B3/T** is the right choice.

B3/T es un altavoz multipunto diseñado para ser discreto y elegante.

Con un rendimiento, calidad sonora y fiabilidad indiscutibles, la **B3/T** es la decisión acertada.

MAIN FEATURES

3" woofer, 0.5" Mylar tweeter.

Internal crossover which delivers each frequency band to its corresponding transducer with minimum loss.

16 Ω impedance. Up to 8 cabinets can be installed in parallel on each channel of a low-impedance amplifier.

Compatible with our HD and SD Amplifiers.

Built-in 100 V line transformer with impedance/power switch selector.

Protective front grille.

Standard bracket included for straightforward installation.

Available colours: arctic white and onyx black.

CARACTERÍSTICAS PRINCIPALES

Woofer de 3", Tweeter de ½" de Mylar.

Filtro pasivo que divide las frecuencias correspondientes a cada transductor con mínimas pérdidas.

Impedancia de 16 Ω para poder instalar hasta 8 cajas en paralelo por canal con un amplificador de baja impedancia.

Uso compatible con nuestros amplificadores de la serie HD y SD.

Transformador incorporado para conexión a línea de 100 V, con un selector de impedancia/potencia.

Reja protectora frontal.

Soporte incluido para una fácil y cómoda instalación.

Colores disponibles: blanco ártico y negro ónix.

B3/T

3" MULTIPOINT SPEAKER



FRONT VIEW WITHOUT GRILLE

SIDE VIEW

REAR VIEW

TECHNICAL FEATURES

Power Handling R.M.S. Program

10 W (direct)
20 W (direct)

100 V Line-1.5W/3W/6W

Switch selectable

Sensitivity 1W/1m

86 dB

Impedance

16 Ω (direct)

100V Line-6k6 Ω /3k3 Ω /1k6 Ω

Switch Selectable

Frequency Response (-10 dB)

120 Hz - 19 kHz

Components

LF-MF

1x 3" Woofer

HF

1/2" Mylar diaphragm

Directivity (HxV)

90° x 50°

Connections

Push Terminals

Dimensions (HxWxD)

141 x 95 x 101 mm

Weight

0.8 kg

B3/T