N12KTU

12" TWO-WAY PASSIVE FULL-RANGE SPEAKER SYSTEM FOR KTV ENTERTAINMENT













The perfect solution for karaoke applications. Superb vocal articulation, powerful low end and crystal clear high frequencies give N12KTV a unique balance in its class.

KEY FEATURES

TRANSDUCERS TECHNOLOGY

Two-way full range passive speaker system composed by one direct radiating 3-inch voice coil, 12" loudspeaker and one 1.75-inch voice coil diameter, PETP diaphragm, neodymium magnet compression driver loaded to an asymmetrical rotational horn (50° to 100° x 55° dispersion).

POWER & CONTROL

800 W continuous power in musical program.

An accurate internal passive crossover achieves an optimum performance while including a protection on high frequency driver.

Connectors are placed on an inclined plane to effectively protect them against rain or moisture.

Double Speakon (input & link)

DESIGN & ACCESSORIES

2mm speaker grille with black mesh, exclusively designed with an optimum perforation gradient and attractive appearance.

Multilayer birch plywood cabinet with Polyurea® coating, offering maximum reliability and strength for touring as well as for high demanding applications.

M8 rigging points for easy flying.

M8 socket mounted on the bottom side.

www.amateaudio.com DATA SHEET 1/4

N12KTU

12" TWO-WAY PASSIVE FULL-RANGE SPEAKER SYSTEM FOR KTV ENTERTAINMENT





TECHNICAL FEATURES

De la Caracteria		200 W
Power (musical program)		800 W
Power (r.m.s)		400 W
Nominal Impedance		8 Ω
SPL(1W/1m)		98 dB
Maximum SPL (continuous/1m)		127 dB
Maximum SPL (peak/1m)		130 dB
Crossover frequency		2k3 Hz
Frequency Response (-10dB)		70 Hz – 20 kHz
Components	LF-MF HF	12" woofer (3" voice coil)
		1.75" PETP diaphragm neodymium magnet compression driver
Directivity (H x V)		50° to 100° x 55°
Directivity factor (Q)		12.6
Directivity Index (DI)		11 dB
Weight		21.5 Kg
Finish		Multilayer birch plywood with high resistant black Polyurea® coating
Dimensions (H x W x D)		630 x 372 x 404 mm
Grille		2 mm steel with black acoustic mesh
Rigging		M8 points
Connectors		1x Speakon input / 1x Speakon link

DISCOVER NÍTID



UNIQUE DESIGN

Distinguishing details include the speaker grille, exclusively designed for an attractive appearance, maximum protection, and with **the best perforation coefficient in the market, for improved sound quality.** The Polyurea® finish offers durable protection for the birch-ply cabinet. A wide range of accessories is provided for whatever your application is.



THE PERFECT BALANCE

NÍTID series is the culmination of an intensive program of research, development and optimization, to achieve the greatest possible power and performance from the most compact sized cabinet. Every aspect of its form factor has resulted from examination and consideration of optimum acoustic response, ergonomics, construction and appearance.



TOP VIEW



BOTTOM VIEW



SIDE VIEW



FRONT VIEW



REAR VIEW


N12KTU

12" TWO-WAY PASSIVE FULL-RANGE SPEAKER SYSTEM FOR KTV ENTERTAINMENT







FREQUENCY RESPONSE 1w/1m




HORIZONTAL COVERAGE




DIRECTIVITY INDEX (DI)




VERTICAL COVERAGE




HORIZONTAL BEAMWIDTH (-6dB point)



CAD DRAWING SCHEME



VERTICAL BEAMWIDTH (-6dB point)



www.amateaudio.com DATA SHEET 3/4





ASYMMETRICAL DISPERSION HORN

It allows to optimize the coverage depending on its position.

